



Image for the product family

Pisa AS LED 600 17W 1610lm 840 RF White DALI TH5

An asymmetric luminaire designed for installation into modular ceiling 600x600 with a visible support structure and into plaster-cardboard ceiling. Designed for school boards and shop shelves.



BASIC INFORMATION

Index: CA001.1166.840.D020

EAN: 5904312800424

Installation: Into modular ceiling 600x600 with a visible supported structure or into plaster cardboard ceiling

Power: 220 ... 240

Technical data

MECHANICAL DATA

Housing material	Steel sheet
Designed for light-line	yes

OPTICAL DATA

Louver/ diffuser	RF
Reflector	high gloss

ELECTRICAL DATA

Light source	LED
Luminaire power	17 W
Type of equipment	AC
Voltage rating	220 ... 240 V
Through wiring	TH5
Type of driver	DALI
Emergency module	No
Motion sensor	No

LIGHT DATA

Luminaire luminous flux	1610 lm
Luminaire's luminous efficacy	95 lm/W
Color rendering index	80
Light distribution	DI
Colour temperature	4000K
CRI & colour temperature	840

INFORMATION DATA

Net weight	1.5 kg
Colour	White
Power and luminous flux tolerance	+/-10%

CERTIFICATES

Degree of protection (IP)	IP20
Impact resistance	IK03
Class of protection	I
CE	yes
HACCP+	yes
EAC	yes

Dimensions

L	W
595	180

L - Length
W - Width

